

# EK 215 Instructions for Polaris RZR or RZRS Door Enclosure

## **Parts List:**

1-left sideview enclosure  
1-right sideview enclosure  
1-roll of Velcro  
2-JStrips  
12- self tapping screws

## **Tools Needed:**

Scissors or Knife



Toll Free 1-877-444-4147  
www.Jstrongindustries.com

## **Installation Instructions:**

### **Step 1:**

Lay side panels on a clean, dry surface and allow them to warm up to room temperature to produce a tight fit.

### **Step 2**

Align and attach the side panel to roll bar. If you are installing side panels with a JStrong top remove the wedge shape piece at the top of the enclosure.

**Figure 1.** Install the J-Strip and fasten to the side of the roof with the self tapping screws as shown in **Figure 2.**

### **Step 3:**

Clip Jstraps into the front and rear fender wells as shown in **Figure 3.**

\*If you are installing side panels on a RZRS model you will need to remove the Fender flares and then reinstall them over the side panel as shown in

### **Figure 4.**

### **Step 4:**

Install adhesive back Velcro (hookside) along the roll bar and align with the loopside that is sewn into the side panel as shown in **Figure 5.**

### **Step 5:**

Installation is complete.

## **Repeat all 4 steps for the other doors side enclosure**

\*Remove rear dust guard and zip out windows completely prior to transporting on highways were speeds may exceed 55 mph

\*Your new rear dust guard and side enclosure is made of the highest quality clear flexible acrylic. It will, however; scratch if not handled correctly.

Fig 1



Fig 2



Fig 3



Fig 4

